

Leica HDS6200

Latest generation of ultra-high speed laser scanner

Max
scan rate
> 1mio points/
second



Compact design and high-performance scanning optimize field productivity

Latest standard for phase-based scanners

The "next-generation" Leica HDS6200 significantly reduces field costs and increases phase-based data quality for many types of as-built and site surveys where users want to take advantage of ultra-high speed, phase-based laser scanning.

Scan >1 million points per second

The Leica HDS6200 offers users the fastest scan rates available for high-accuracy, as-built surveys, making it the ideal instrument when very short time windows are available for capturing High-Definition Survey™ data.

Highly portable and field-efficient

With scanner, data storage, scanner control, and batteries integrated into a single unit, the Leica HDS6200 is easy to setup and carry for fast project execution. In addition,

the excellent range at which users can achieve high-accuracy scan data combined with the HDS6200's dual-axis (tilt) sensing capability reduce the number of instrument and target setups, further cutting field time. These same features plus its extended temperature capability also increase the versatility of phase-based scanning.

Flexible scan control & registration options

Users can choose from three scanner control options. A side touch panel allows simple control. An optional wireless PDA allows "touch-free" control, plus visual inspection of jpeg scan images. For full 3D viewing, scan measurement, and rigorous quality assurance (QA), users can opt for powerful laptop control with Leica Cyclone SCAN, the industry's most popular and versatile scanner control software. For accurately registering (or stitching) multiple scans together, Leica Cyclone REGISTER software lets Leica HDS6200 users take advantage of either scan targets or "cloud-to-cloud" registration methods that don't require targets.

- when it has to be **right**

Leica
Geosystems

Leica HDS6200

Product Specifications

General	
Instrument type	Compact, phase-based, dual-axis sensing, ultra high-speed laser scanner, with survey-grade accuracy and full field-of-view
User interface	Onboard touch panel, or external notebook or Tablet PC, or PDA
Scanner drive	Servo motor
Data storage	Integrated hard drive
Camera	No integrated camera; Cyclone SCAN supports use of external camera

System Performance	
Accuracy of single measurement	
Position*	5 mm, 0.4 m to 25 m range; 9 mm to 50 m range
Distance*	≤2 mm at 90% albedo up to 25 m; ≤3 mm at 18% albedo up to 25 m ≤3 mm at 90% albedo up to 50 m; ≤5 mm at 18% albedo up to 50 m
Angle (horizontal/vertical)	125 μrad/125 μrad, one sigma
Modeled surface precision**/noise	1 mm at 25 m; 2 mm at 50 m for 90% albedo, one sigma; 2 mm at 25m; 4 mm at 50m, for 18% albedo, one sigma
Target acquisition***	2mm std. deviation
Dual-axis sensor	Selectable on/off; 3.6" resolution
Data integrity monitoring	Self-check at start-up; optional checks using Cyclone-SCAN

Laser Scanning System			
Type	Phase-shift		
Laser Class	3R (IEC 60825-1)		
Range	79 m ambiguity interval 79 m @90%; 50 m @18% albedo		
Scan rate	Up to 1,016,727 points/sec, maximum instantaneous rate		
Scan resolution	3 mm at exit (based on Gaussian definition) + 0.22 mrad divergence; 8 mm @25 m; 14 mm @50 m		
Spot size	3 mm at exit (based on Gaussian definition) + 0.22 mrad divergence; 8 mm @25 m; 14 mm @50 m		
Selectability	5 pre-set spacings per table		
	Pts/360°	Scan time	Point spacing
	(vert., horiz.)	(full dome)	at range @10 m
"Preview"	1250	25 sec	50.6x50.6 mm
Middle (4x)	5000	1 min 40 sec	12.6x12.6 mm
High (8x)	10000	3 min 22 sec	6.3x6.3 mm
Super High (16x)	20000	6 min 44 sec	3.1x3.1 mm
Ultra High (32x)	40000	26 min 40 sec	1.6x1.6 mm
Field-of-view	Horizontal 360° (maximum) Vertical 310° (maximum)		
Aiming/Sighting	Optical horizontal sighting using QuickScan™ feature		
Scanning Optics	Vertically rotating mirror on horizontally rotating base; User selectable vertical rotation speed (12.5 rps, 25 rps or 50 rps); Environmentally protected by shield		
Scan motors	Direct drive, brushless; proprietary		
Data transfer	Ethernet or USB 2.0 device (two ports)		
Data storage capacity (onboard)	60 GB, min		
Communications	Ethernet or integrated Wireless LAN (WLAN)		
Status indicators	4-line alphanumeric display for laser status, system power & status 1 LED for laser status		
Level indicator	External bubble; digital readout on touch panel or via laptop		

Electrical	
Power supply	24 V DC; 90 – 260 V AC
Power Consumption	65 W max.
Battery Type	Integrated: Li-ion, External: sealed lead acid
Duration	Internal: 2.5 hrs, typical, External: 4 hrs, typical
Power status	LEDs indicate charging status and capacity levels

Environmental	
Operating temp.	-10° C to +45° C
Storage temp.	-20° C to +50° C
Lighting	Fully operational between bright sunlight and complete darkness
Humidity	Non-condensing
Reflectivity	no retro-reflectors

System Performance	
Scanner	
Dimensions	7.8"Dx11.6" Wx16.5" H, 199 mm Dx294 mm Wx360 mm H
Weight	14 kg, nominal (includes integrated battery)
Battery (external)	
Dimensions	9.5" Dx10" Wx12" H, 240 mm Dx260 mm Wx300 mm H
Weight	16 kg, nominal
AC Power Supply	
Dimensions	9.5" Dx5" Wx6" H, 240 mm Dx127 mm Wx152 mm H
Weight	2.5 kg, nominal

Standard Accessories	
Scanner and accessory carrying case	
Additional rechargeable integrated battery	
Charging/power cable, ethernet cable, A/C cable	
Battery charger / A/C power supply	
Battery charging cradle for internal battery	
Cyclone™-SCAN software	
Cleaning kit	

Hardware Options	
Notebook PC, Tablet PC, or PDA	
HDS6200 scan targets and target accessories	
Service agreement for Leica HDS6200	
Extended warranty for Leica HDS6200	
External camera kit (third party product)	

Notebook PC for scanning ^Δ	
Component	required (minimum)
Processor	1.7 GHz Pentium M or similar
RAM	1024 MB SDRAM (2 GB for Vista)
Network card	Ethernet
Display	SXGA+ (64 MB or greater video RAM rec.)
Operating system	Windows XP Professional (SP2 or higher) (32 or 64) Windows Vista (32 or 64)

Control Options	
Leica Cyclone SCAN software (see Leica SCAN data sheet for full list of features)	
Onboard touch panel	
Web browser	

Ordering Information, including upgrade from Leica HDS6000 or HDS6100	
Contact Leica Geosystems or authorized representatives	

All specifications are subject to change without notice.

All +/- accuracy specifications are one sigma unless otherwise noted.

¹ SmartScan™ technology feature

^Δ Minimum requirements for modeling operations are different. Refer to Cyclone data sheet specifications.

* At 127,000 pts/sec scan rate, one sigma

** At 127,000 pts/sec scan rate, one sigma;

subject to modeling methodology for modeled surface

*** Algorithmic fit to planar HDS gray & white targets

Laser class 3R in accordance with IEC 60825-1 resp. EN 60825-1

Windows is a registered trademark of Microsoft Corporation. Other trademarks and trade names are those of their respective owners.

Illustrations, descriptions and technical data are not binding. All rights reserved.
Printed in Switzerland – Copyright Leica Geosystems AG, Heerbrugg, Switzerland, 2010.
782705en – VII.10 – RDV

Leica Geosystems AG
Heerbrugg, Switzerland

www.leica-geosystems.com/hds

- when it has to be **right**

Leica
Geosystems