

Leica ScanStation P20

Industry's Best Performing Ultra-High Speed Scanner



Unprecedented performance in ultra-high speed laser scanning

Productivity & Accuracy

An innovative combination of advanced time-of-flight range measurement plus modern Waveform Digitising (WFD) technology enables the compact Leica ScanStation P20 to achieve ultra-high scan speeds and low-noise performance at extended range (to 120 m). Together with high-accuracy angular measurements and survey-grade tilt compensation, Leica ScanStation P20 delivers unprecedented ultra-high speed scan data quality for as-built and scene surveys.

Scan up to 1 million points per second

Leica ScanStation P20 is the ideal instrument when very short time windows are available for capturing High-Definition Survey™ data or when ultra-high density, full dome scan data is needed for client deliverables.

Unprecedented environmental capabilities

Developed and manufactured by Leica Geosystems, Leica ScanStation P20 lets users apply ultra-high speed scanning in operating temperatures ranging from -20° C to +50° C. Moreover, with an Ingress Protection rating of IP54 and a Class 1 laser safety rating, users can reap the benefits of ultra-high speed scanning for even more sites and projects.

"Check & Adjust" for added confidence

Leica ScanStation P20 is the first laser scanner to feature a valuable "Check & Adjust" capability. Instead of sending the instrument to a service centre, users can electronically check the accuracy of their ScanStation P20 themselves and automatically adjust instrument parameters to ensure the highest level of performance.

- when it has to be **right**

Leica
Geosystems

Leica ScanStation P20

Product Specifications

General	
Instrument type	Compact, ultra-high speed pulsed laser scanner with survey grade accuracy, range and field-of-view; integrated camera and laser plummet
User interface	Onboard control, notebook or tablet PC, PDA
Data storage	Integrated solid-state drive (SSD) or external USB flash drive
Camera	Auto-adjusting, integrated high-resolution digital camera with zoom video

System Performance	
Accuracy of single measurement	3D Position Accuracy
	3 mm at 50 m; 6 mm at 100 m
	Linearity error
	≤ 1 mm
	Angular accuracy
	8" horizontal; 8" vertical
Target acquisition*	2 mm standard deviation up to 50 m
Dual-axis compensator	Selectable on/off, resolution 1", dynamic range +/- 5', accuracy 1.5"

Laser Scanning System																																																												
Type	Ultra-high speed time-of-flight enhanced by Waveform Digitising (WFD) technology																																																											
Wavelength	808 nm (invisible)																																																											
Laser class	1 (in accordance with IEC 60825-1)																																																											
Range	Up to 120 m; 8% reflectivity (minimum range 0.1 m)																																																											
Scan rate	Up to 1'000'000 points/s																																																											
Range noise**	<table border="1"> <thead> <tr> <th>Range</th> <th>Black (8%)</th> <th>Gray (40%)</th> <th>White (90%)</th> </tr> </thead> <tbody> <tr> <td>10 m</td> <td>1.4 mm rms</td> <td>0.8 mm rms</td> <td>0.6 mm rms</td> </tr> <tr> <td>25 m</td> <td>0.7 mm rms</td> <td>0.4 mm rms</td> <td>0.4 mm rms</td> </tr> <tr> <td>50 m</td> <td>0.6 mm rms</td> <td>0.4 mm rms</td> <td>0.4 mm rms</td> </tr> <tr> <td>100 m</td> <td>1.5 mm rms</td> <td>1.0 mm rms</td> <td>0.9 mm rms</td> </tr> </tbody> </table>	Range	Black (8%)	Gray (40%)	White (90%)	10 m	1.4 mm rms	0.8 mm rms	0.6 mm rms	25 m	0.7 mm rms	0.4 mm rms	0.4 mm rms	50 m	0.6 mm rms	0.4 mm rms	0.4 mm rms	100 m	1.5 mm rms	1.0 mm rms	0.9 mm rms																																							
Range	Black (8%)	Gray (40%)	White (90%)																																																									
10 m	1.4 mm rms	0.8 mm rms	0.6 mm rms																																																									
25 m	0.7 mm rms	0.4 mm rms	0.4 mm rms																																																									
50 m	0.6 mm rms	0.4 mm rms	0.4 mm rms																																																									
100 m	1.5 mm rms	1.0 mm rms	0.9 mm rms																																																									
Scan time and resolution	<table border="1"> <thead> <tr> <th rowspan="2">10 pre-set point spacings mm at 10 m</th> <th colspan="4">Quality level</th> </tr> <tr> <th>1</th> <th>2</th> <th>3</th> <th>4</th> </tr> </thead> <tbody> <tr> <td>50</td> <td>00:20</td> <td>00:20</td> <td>00:20</td> <td>00:20</td> </tr> <tr> <td>30</td> <td>00:29</td> <td>00:29</td> <td>00:29</td> <td>00:29</td> </tr> <tr> <td>20</td> <td>00:39</td> <td>00:39</td> <td>00:39</td> <td>00:44</td> </tr> <tr> <td>15</td> <td>00:50</td> <td>00:50</td> <td>00:50</td> <td>01:13</td> </tr> <tr> <td>10</td> <td>01:11</td> <td>01:11</td> <td>01:23</td> <td>02:40</td> </tr> <tr> <td>8</td> <td>01:26</td> <td>01:26</td> <td>02:07</td> <td>04:09</td> </tr> <tr> <td>5</td> <td>02:13</td> <td>02:42</td> <td>05:18</td> <td>10:33</td> </tr> <tr> <td>4</td> <td>02:45</td> <td>04:10</td> <td>08:16</td> <td>16:29</td> </tr> <tr> <td>2</td> <td>08:17</td> <td>16:29</td> <td>32:56</td> <td>1:05:50</td> </tr> <tr> <td>1</td> <td>32:56</td> <td>1:05:50</td> <td>2:11:38</td> <td>----</td> </tr> </tbody> </table>	10 pre-set point spacings mm at 10 m	Quality level				1	2	3	4	50	00:20	00:20	00:20	00:20	30	00:29	00:29	00:29	00:29	20	00:39	00:39	00:39	00:44	15	00:50	00:50	00:50	01:13	10	01:11	01:11	01:23	02:40	8	01:26	01:26	02:07	04:09	5	02:13	02:42	05:18	10:33	4	02:45	04:10	08:16	16:29	2	08:17	16:29	32:56	1:05:50	1	32:56	1:05:50	2:11:38	----
10 pre-set point spacings mm at 10 m	Quality level																																																											
	1	2	3	4																																																								
50	00:20	00:20	00:20	00:20																																																								
30	00:29	00:29	00:29	00:29																																																								
20	00:39	00:39	00:39	00:44																																																								
15	00:50	00:50	00:50	01:13																																																								
10	01:11	01:11	01:23	02:40																																																								
8	01:26	01:26	02:07	04:09																																																								
5	02:13	02:42	05:18	10:33																																																								
4	02:45	04:10	08:16	16:29																																																								
2	08:17	16:29	32:56	1:05:50																																																								
1	32:56	1:05:50	2:11:38	----																																																								
Field-of-View	Horizontal Vertical																																																											
	360° 270°																																																											
Aiming/Sighting	Parallax-free, integrated zoom video																																																											
Scanning optics	Vertically rotating mirror on horizontally rotating base Up to 50 Hz with internal battery Up to 100 Hz with external power supply																																																											
Data storage capacity	256 GB onboard solid-state drive (SSD) or external USB device																																																											
Communications	Gigabit Ethernet or integrated Wireless LAN																																																											
Integrated colour digital camera with zoom video	Single 17° x 17° image; 5 megapixels; streaming video with zoom; auto-adjusts to ambient lighting																																																											
Onboard display	Touchscreen control with stylus, full colour VGA graphic display (640 x 480 pixels)																																																											
Level indicator	External bubble, electronic bubble in onboard software																																																											
Data transfer	Ethernet, WLAN or USB 2.0 device																																																											
Laser plummet	Laser class 1 (IEC 60825-1) Centering accuracy: 1.5 mm at 1.5 m Laser dot diameter: 2.5 mm at 1.5 m Selectable ON/OFF																																																											

Electrical	
Power supply	24 V DC, 100 – 240 V AC
Power consumption	40 W typical
Battery type	Internal: Li-Ion; External: Li-Ion
Power ports	Internal: 2, External: 1 (simultaneous use, hot swappable)
Duration	Internal > 7 h (2 batteries), External > 8.5 h (room temp.)

Environmental	
Operating temperature	-20° C to +50° C / -4° F to 122° F
Storage temperature	-40° C to +70° C / -40° F to 158° F
Lighting	Fully operational between bright sunlight and complete darkness
Humidity	Non-condensing
Dust/Humidity	IP54 (IEC 60529)

Physical	
Scanner	Dimensions (D x W x H) Weight
	238 mm x 358 mm x 395 mm / 9.4" x 14.1" x 15.6" 11.9 kg / 26.2 lbs, nominal (w/o batteries)
Battery (internal)	Dimensions (D x W x H) Weight
	40 mm x 72 mm x 77 mm / 1.6" x 2.8" x 3.0" 0.4 kg / 0.9 lbs
Battery (external)	Dimensions (D x W x H) Weight
	95 mm x 248 mm x 60 mm / 3.7" x 9.8" x 2.4" 1.9 kg / 4.2 lbs
AC Power Supply	Dimensions (D x W x H) Weight
	170 mm x 85 mm x 42.5 mm / 6.6" x 3.3" x 1.6" 0.86 kg / 1.9 lbs
Mounting	Upright or upside down

Standard Accessories Included	
Scanner transport case	
Tribrach (Leica Professional Series)	
4 x Internal batteries	
Battery charger / AC power cable, Car adapter, Daisy chain cable	
Data cable	
Height metre and distance holder for height metre	
1 year CCP Basic support contract	

Additional Accessories & Services	
B&W scan targets and target accessories	
Range of Customer Care Products (CCPs) that include Support, Hardware & Software maintenance and Extended warranty.	
External battery with charging station, AC power supply and power cable	
Professional charger for internal batteries	
AC power supply for scanner	
Tripod and tripod star	
Upside down mounting adapter	

Control Options	
Full colour touchscreen for onboard scan control.	
Remote control: Leica CS10/CS15 controller or any other remote desktop capable device, including iPad, iPhone and other Smartphones.	

Ordering Information	
Contact your local Leica Geosystems representative or an authorised Leica Geosystems dealer.	

All specifications are subject to change without notice.
All accuracy specifications are one sigma unless otherwise noted.
* Algorithmic fit to planar B&W targets
** Detailed explanation on request

Scanner: Laser class 1 in accordance with IEC 60825-1 resp. EN 60825-1
Laser plummet: Laser class 1 in accordance with IEC 60825-1 resp. EN 60825-1

iPhone and iPad are trademarks of Apple Inc.

Illustrations, descriptions and technical data are not binding. All rights reserved. Printed in Switzerland – Copyright Leica Geosystems AG, Heerbrugg, Switzerland, 2012.
795781en – VIII.12 – galledia

